



## LUMINOUS PAINT

<p><b>Product description</b></p>	<p>A photoluminescent translucent matt paint, which collects and stores light, then glows in the dark for hours! Creating luminous surfaces of scenery, skies, secret signs, arrows... throughout the home it is ideal for children's rooms, stairs, etc. and safe! Luminous Paint gives a translucent satin finish and can be applied to unpainted and previously painted surfaces such as wood, plaster, cement, cardboard etc. It may also be tinted, however this does reduce the luminescence, a small amount of pastel colours only should be used.</p>
<p><b>Surface preparation</b></p>	<p>Surfaces must be clean, dry; free of oil and grease and in good sound condition. Remove all loose and flaking material back to a sound surface and edge. Smooth and old paint surfaces should be lightly sanded to form a key. Bare surfaces, new or special surfaces (plastic, glass, ceramics, metal etc.) should be primed with the appropriate Oxi product.</p>
<p><b>Application</b></p>	<p>Ready to use.</p> <p>Stir well before and during use.</p> <p>Apply a thick layer (luminescence is stronger) to the stencil or the design that has been marked out using a good quality brush.</p>
<p><b>Good application practice</b></p>	<p>Close container after use and store in a cool dry place.</p> <p>Keep from freezing.</p> <p>Apply between 10°C and 25°C. High humidity slows the drying time of the paint.</p>



### Technical data





<b>CLASSIFICATION</b>	Family 1 - Class 7b2 according to standard NFT 36-005.
<b>VEHICLE TYPE</b>	Acrylic resins
<b>SPECIFIC GRAVITY (at 25°C)</b>	1.18 ± 0.02
<b>VISCOSITY (at 25°C)</b>	20 - 22
<b>FINISH</b>	Matt
<b>ODOUR</b>	Odourless
<b>DRYING TIME</b>	Touch dry 30 min.
<b>COVERAGE</b>	± 2m <sup>2</sup> per 250 ml.
<b>CLEAN-UP</b>	Warm soapy water.
<b>APPLICATIONS TOOLS</b>	Brush, Roller.
<b>VOC</b>	EU limit value for this product (cat. A/i): 140 g/l (2010). This product contains max 16 g/l.

### Safety:

Contains 1,2-benzisothiazol-3 (2H) -one. May produce an allergic reaction. Help preserve the environment. Do not dispose of left over product down drains. Empty containers should be disposed of in accordance with local regulations. Contact your local authority for information regarding the disposal of any leftover product.

### Sizes

250 ml

Where to use	Clean-up	Application Tools	Drying
 Interior			 30 mn



This notice supersedes all previous sheets relative to the same product. Its purpose is to inform our customers about the properties of our product. The information contained herein is based on our present knowledge, however, we are unable to guarantee results as we have no control over the conditions under which our products are applied. Technology is continually developing and it is the responsibility of the end user before commencing work, to check with our departments that this information has not been modified in a more recent version. This information is correct at date of issue - October 2015.

» MSDS available from our website (see below)